

## **STOCK-ade Petrol Compressor**

## **Features**

#### 6hp Premium Gas Engine

Designed specially for use with STOCK-ade Fencing Staplers (ST-315 and ST-400) Genuine Subaru Engine Made in the USA Reliable performance for all weather, every day fencing 12 month limited warranty

#### **Auto Variable Speed Control**

Engine idles when not under demand load Lowers emissions Reduces noise

#### **Overhead Drive Design**

Easy starting at low temperatures Smoothe engine performance Superior fuel efficiency

#### **Corrosion Resistant Air Pump Housing**

Lightweight High durability

#### **Patented Pump Design**

Increased cooling efficiency for durability Reduced operating temperature

#### **Rugged Frame Construction**

Lightweight for portability Frame clamp or tie points to secure for portability

### Fully Equipped for Use

Just add fuel

# Toll Free Customer Help Line USA and Canada 1-888-895-4549

#### **CE Compliant**



Product Code	Description	Barcode
C10066	STOCK-ade Petrol Compressor	9315104016392



Oil Type - General Use

# **STOCK-ade Petrol Compressor**

Specifications - Compressor - Pump			
Product Size (WxHxD) Packaged Size (WxHxD) Tool Weight	22 <sup>7</sup> / <sub>8</sub> " x 19 <sup>1</sup> / <sub>4</sub> " x 20" (580 x 490 x 490mm) 24 <sup>3</sup> / <sub>8</sub> " x 21 <sup>1</sup> / <sub>2</sub> " x 20" (620 x 546 x 508mm) 81.4lb (37kg)		
Quantity Per Pack Quantity Per Pallet	1 8		
Maximum Operating Pressure	155psi (10.7 bar)		
Optimum Operating Pressure	90-120psi regulated air (6.2-8.3 bar)		
Receiver Capacity	4 Gallons (15.1 ltr)		
Air output at 90psi (6.2 bar) Recommended Air Hose Fitting Diameter	5 cfm @ 90psi (6.2 bar) ³⁄₅" (10mm)		
Engine Specifications			
Engine Type	4 Stroke, overhead cam, single cylinder		
Engine Type Engine Displacement	4 Stroke, overhead cam, single cylinder 9.8 cu-in (160cm <sup>3</sup> )		
Engine Displacement	9.8 cu-in (160cm <sup>3</sup> )		
Engine Displacement Max Output @ 3,600 rpm	9.8 cu-in (160cm <sup>3</sup> ) 5.0 bhp (3.7kW)		
Engine Displacement Max Output @ 3,600 rpm Oil Capacity	9.8 cu-in (160cm <sup>3</sup> ) 5.0 bhp (3.7kW) 0.61 US qt (0.58 ltr)		

Please refer to operating manual for specific details regarding engine performance

 Applications

 Ideal for use with STOCK-ade Fencing Stapler Tools

 Oilless air compressor applications

 Rural environments where transportability is required over rough terrain

SAE 10W-30

The information presented in this product information sheet is correct as at the date of publication. STOCK-ade reserves the right to change performance, product or content information without notice. READ ALL SAFETY INSTRUCTIONS