

Pneumatic ST-315 Hot Dipped Galvanised Fence Batten Staples

Features

World's Only Power-Driven 3.15mm Diameter Staple

Narrow Crown

Grips the fence wire for improved holding power

Divergent Point

Staple legs spread as they are driven into timber battens for superior holding power
Minimize water tracking

3.15mm Wire Diameter

Professional grade fencing staple
Suitable for use on the high density, dry timber

33 and 40mm Staple Lengths

Superior holding power
33mm designed for rural wire fences
40mm designed for mesh and woven wire fences

Genuine STOCK-ade Paper Collation

Superior collation strength
Reduced tool contamination
Moisture resistant adhesive formula for improved all weather performance

Hot Dipped Galvanised (Class 3 Wire)

Extreme durability for long life
Manufactured from Bezinal 2000 240gm
high life pre-galvanised wire

Made in New Zealand

Tested in extreme conditions

Designed for use with STOCK-ade ST-315 Fencing Stapler (A12505)



Product Code	Description	Barcode
A12530	STOCK-ade Pneumatic 33 x 3.15mm HD Galvanised DP Fence Batten Staple 2700	9315104016118
A12535	STOCK-ade Pneumatic 40 x 3.15mm HD Galvanised DP Fence Batten Staple 2100	9315104016125

Pneumatic ST-315 Hot Dipped Galvanised Fence Batten Staples

Specifications	A12530	A12535
Packaged Size (WxHxD)	225 x 88 x 135mm	225 x 88 135mm
Packaged Weight	8.8kg	9.6kg
Pallet Size (WxD)	710 x 780mm	
Pallet Quantity	75 cartons	75 cartons
Quantity Per Pack	2,700	2,100
Staple Type	Divergent point fencing staple	
Collation Type	Paper collated	
Tool Magazine Capacity	80 staples (approx 3 strips)	

Applications	
	Rural livestock fencing
	Horticulture
	Rural light mesh and light woven fencing
	Predator control fencing
	Plastic mesh, pet enclosures and poultry fencing
	Rural utilities applications
	Cladding

ST-315TM

